



NOBLE PLASTICIZER

PRODUCT DESCRIPTION	Noble Plasticizer is designed to increase Flexibility, impact resistance, chip resistance, And U.V. protection in Noble Top Coat 2K Products, it mixes easily and does not affect Dry or cure times
FEATURES	01. Flexible additive. 02. Highly versatile and compatible to Noble Products. 03. General Purpose Item and compatible with Noble products.
RECOMMENDED USE	To improve the flexibility of Noble 2K primer Noble top coat 2K, and Noble clear coat 2K and over a wide variety of semi-rigid and flexible plastic parts.
SURFACE PREPARATION	Surface should be well prepared to obtain excellent smooth surface. At the time of application it should be clean and dry.

TECHNICAL INFORMATION

COLORS	Slightly Yellowish.
FLASH POINT	27°C
VOLATILE ORGANIC COMPOUNDS (VOC)	550.0 gm/liter

APPLICATION DATA

	MIXING RATIO	5 - 10% for a liter of paint to be added at spraying viscosity mix well after application.
	POT LIFE @ 25°C	3 - 4 hrs. After mixing

MISCELLANEOUS DATA

STORAGE	The product must be stored according to Noble Regulations. The product should be kept in cool and well ventilated place, protected from heat and direct sunlight at temp 5 - 35°C. Containers must be kept tightly closed.
SAFETY / HEALTH	Ensure good ventilation during application and drying. Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. Keep out of reach of children.



NOBLE PLASTICIZER

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.

