

NOBLE DY WOOD STAIN

PRODUCT DESCRIPTION	It is a fast drying universal wood stain. It can be easily applied on wood to give various transparent colours. The product has been specifically designed as per market quality and requirements.
RECOMMENDED USES	For application of various types of wood to give better look, colour and appearance. It can be overcoated by using Noble Synthetic Varnish, PU Clear, NC Clear or Acrylic Clear.

TECHNICAL DATA

COLOUR, DRY FILM	Limited Colours
FINISH, DRY FILM	Transparent - Matt
SPECIFIC GRAVITY	0.90 ± 0.05
THEORETICAL SPREADING	10 - 12 M ² /LTR, indicative, depends on type of wood.
FLASH POINT	20°C

DRYING TIME

Drying time @ 30°C (Temperature, humidity, air movement, 1m thickness and number of coats all affect the drying time.)

TOUCH DRY	5 - 10 minutes
DRY TO RECOAT	30 - 40 minutes

ADVANTAGES

NOBLE DY WOOD STAIN SYSTEM	Easy to apply, gives new look to wooden surface, transparent colours, can be overcoated with various types of wood finishes.
-----------------------------------	--

APPLICATION INSTRUCTION

SURFACE PREPARATION	Before application, the surface should be sound, clean and free from oil, grease, loose particles, dust, etc. Application can be done by the recommended application methods.
----------------------------	---



NOBLE DY WOOD STAIN

APPLICATION DATA	
APPLICATION METHOD	Cloth or Spray
CLEANING/THINNING	Noble G.P. Thinner
THINNER (VOLUME)	Ready to use
CONV. SPRAY REQUIREMENTS	Atomizing Pressure : 50 psi
NOZZLE SIZE	0.017" – 0.020"

SYSTEM							
RECOMMENDED SYSTEM To be applied on prepared surface.	<p style="color: #c00000; font-weight: bold;">For wooden surface:</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 70%;">Noble DY Wood Stain (Market Quality)</td> <td style="width: 30%; text-align: right;">: 1 – 2 coats</td> </tr> <tr> <td>Noble PU Wood Sanding Sealer (4:1 /2:1) (OR) Noble NC Sanding Sealer</td> <td style="text-align: right;">: 1 – 2 coats</td> </tr> <tr> <td>Noble P.U. Wood Clear (4:1 / 2:1) (OR) Noble NC Clear</td> <td style="text-align: right;">: 1 – 2 coats</td> </tr> </table>	Noble DY Wood Stain (Market Quality)	: 1 – 2 coats	Noble PU Wood Sanding Sealer (4:1 /2:1) (OR) Noble NC Sanding Sealer	: 1 – 2 coats	Noble P.U. Wood Clear (4:1 / 2:1) (OR) Noble NC Clear	: 1 – 2 coats
Noble DY Wood Stain (Market Quality)	: 1 – 2 coats						
Noble PU Wood Sanding Sealer (4:1 /2:1) (OR) Noble NC Sanding Sealer	: 1 – 2 coats						
Noble P.U. Wood Clear (4:1 / 2:1) (OR) Noble NC Clear	: 1 – 2 coats						

ADDITIONAL DATA	
SHELF LIFE @ 30°C	12 months, in original sealed container, with proper storage conditions.

HEALTH & SAFETY	
SAFETY PRECAUTIONS	<p>As a general rule, avoid skin and eye contact by wearing overalls, gloves, goggles, and mask etc. Spillage on skin should immediately be removed by thorough washing with water and soap or suitable cleaner. Eye should be flushed with fresh water. Avoid inhalation of vapours and paint mist by wearing suitable mask. In the event of ingestion and eye contact, seek medical attention immediately. Painting must be carried out in well-ventilated area.</p> <p>This product contains flammable materials and should be kept away from the sparks and open flames, smoking in the area should not be permitted. Local safety regulations should be followed.</p>



NOBLE DY WOOD STAIN

STORAGE & HANDLING

STORAGE

Store the paint in proper storage conditions as per the local regulations. Keep the paint container in sealed condition under shed, away from direct sunlight and extreme temperatures. Do not stock paint material near to any ignition sources. Do not put back the half or unused material back in original container, containing the supplied paint, to avoid contamination. Handle with care. Stir well before use.

NOTE : We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests.
We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data.

This data sheet supersedes all previous issued.
Issued: 0718

